




# EB Series (100M) HDBaseT HDMI Full HD, 4K Extender



HDBaseT technology is a consumer electronic (CE) connectivity technology optimized for whole-home and commercial multimedia distribution.



**EB-100-TR**  
**100M**  
**Extender Set**

**EAWP-VH100-TR**  
**100M HDMI, VGA Wall**  
**Plate Extender Set**

**EAWP-100-TR**  
**100M Wall Plate**  
**Extender Set**

**EAWP-100-R**  
**100M Wall Plate**  
**Receiver**

Transmitter: EB-100-T  
Receiver: EB-100-R  
Distance: 100m (1080P)  
HDMI Max Resolution: 4K 60Hz (4:2:0)  
4K 30Hz (4:4:4)  
3D: Yes  
Cable: Cat5e/6/6A  
POC: Either side (12V, 2A)  
HDCP Compliant: Yes  
Transmitter Dimension: 115x84x16mm  
Receiver Dimension: 115x84x16mm  
RS-232: Bi-directional  
IR: Yes  
Ethernet: No  
Transmitter: POC On/Off option  
Receiver: POC On/Off option

Transmitter: EAWP-VH100-T  
Receiver: EB-100-R  
Distance: 100m (1080P)  
HDMI Max Resolution: 4K 60Hz (4:2:0)  
4K 30Hz (4:4:4)  
VGA Max Resolution: 1080P  
Switching: Auto, Manual or RS-232  
3D: Yes  
Cable: Cat5e/6/6A  
POC: Either side (12V, 2A) or  
(24V, 1A support for EAWP-VH70-T  
Standalone Uses)  
HDCP Compliant: Yes  
VGA Compliance: VESA  
Transmitter Dimension: 142x85x35mm  
Receiver Dimension: 115x84x16mm  
RS-232: Bi-directional  
IR: No  
Ethernet: No  
Transmitter: Support standard POH/  
POE (48V) with PD option

Transmitter: EAWP-100-T  
Receiver: EB-100-R  
Distance: 100m (1080P)  
HDMI Max Resolution: 4K 60Hz (4:2:0)  
4K 30Hz (4:4:4)  
3D: Yes  
Cable: Cat5e/6/6A  
POC: Either side (12V, 2A)  
HDCP Compliant: Yes  
Transmitter Dimension: 85x85x30mm  
Receiver Dimension: 115x84x16mm  
RS-232: No  
IR: No  
Ethernet: No  
Receiver: POC On/Off option

Receiver: EAWP-100-R  
Transmitter: EB-100-T/EAWP-VH100-T/  
EAWP-100-T (Option items)  
Distance: 100m (1080P)  
HDMI Max Resolution: 4K 60Hz (4:2:0)  
4K 30Hz (4:4:4)  
3D: Yes  
Cable: Cat5e/6/6A  
POC: 12V, 2A  
HDCP Compliant: Yes  
Receiver Dimension: 85x85x30mm  
RS-232: No  
IR: No  
Ethernet: No