





EB Series (70M) HDBaseT HDMI Full HD, 4K Extender



HDBaseT technology is a consumer electronic (CE) connectivity technology optimized for whole-home and commercial multimedia distribution.



EB-70-TR
70M
Extender Set

EAWP-VH70-TR
70M HDMI, VGA Wall
Plate Extender Set

EAWP-70-TR
70M Wall Plate
Extender Set

EAWP-70-R
70M Wall Plate
Receiver

Transmitter: EB-70-T
Receiver: EB-70-R
Distance: 70m (1080P)
HDMI Max Resolution: 4K 60Hz (4:2:0)
4K 30Hz (4:4:4)
3D: Yes
Cable: Cat5e/6/6A
POC: Either side (12V, 2A)
HDCP Compliant: Yes
Transmitter Dimension: 115x84x16mm
Receiver Dimension: 115x84x16mm
RS-232: Bi-directional
IR: Yes
Ethernet: No
Transmitter: POC On/Off option
Receiver: POC On/Off option

Transmitter: EAWP-VH70-T
Receiver: EB-70-R
Distance: 70m (1080P)
HDMI Max Resolution: 4K 60Hz (4:2:0)
4K 30Hz (4:4:4)
VGA Max Resolution: 1080P
Switching: Auto, Manual or RS-232
3D: Yes
Cable: Cat5e/6/6A
POC: Either side (12V, 2A) or
(24V, 1A support for EAWP-VH70-T
Standalone Uses)
HDCP Compliant: Yes
VGA Compliance: VESA
Transmitter Dimension: 142x85x35mm
Receiver Dimension: 115x84x16mm
RS-232: Bi-directional
IR: No
Ethernet: No
Transmitter: Support standard POH/
POE (48V) with PD option

Transmitter: EAWP-70-T
Receiver: EB-70-R
Distance: 70m (1080P)
HDMI Max Resolution: 4K 60Hz (4:2:0)
4K 30Hz (4:4:4)
3D: Yes
Cable: Cat5e/6/6A
POC: Either side (12V, 2A)
HDCP Compliant: Yes
Transmitter Dimension: 85x85x30mm
Receiver Dimension: 115x84x16mm
RS-232: No
IR: No
Ethernet: No
Receiver: POC On/Off option

Receiver: EAWP-70-R
Transmitter: EB-70-T/EAWP-VH70-T/
EAWP-70-T (Option items)
Distance: 70m (1080P)
HDMI Max Resolution: 4K 60Hz (4:2:0)
4K 30Hz (4:4:4)
3D: Yes
Cable: Cat5e/6/6A
POC: 12V, 2A
HDCP Compliant: Yes
Receiver Dimension: 85x85x30mm
RS-232: No
IR: No
Ethernet: No